

PVC PRESSURE PIPE SYSTEMS

PVC-O PIPE SERIES 2

PVC-O PIPES ARE DESIGNED AND MANUFACTURED TO AS/NZS 4441 FOR VARIOUS WATER INDUSTRY APPLICATIONS



PVC-O PIPE SERIES 2 PN16 RRJ

| CODE | SIZE | DESCRIPTION |
|---------|-------|------------------------|
| 1402310 | 100mm | PVC-O PIPE S2 PN16 RRJ |
| 1402272 | 150mm | PVC-O PIPE S2 PN16 RRJ |
| 1402255 | 200mm | PVC-O PIPE S2 PN16 RRJ |
| 1402249 | 225mm | PVC-O PIPE S2 PN16 RRJ |
| 1402257 | 250mm | PVC-O PIPE S2 PN16 RRJ |
| 1402311 | 300mm | PVC-O PIPE S2 PN16 RRJ |
| 700041 | 375mm | PVC-O PIPE S2 PN16 RRJ |

GENERAL APPLICATION

OPVC can be safely used in a wide range of applications including water mains, recycled water, drinking water, irrigation and pressure sewerage applications.

TECHNICAL DATA

Temperature Range: 0°C to 60°C

Joining Methods: Rubber ring joint

Approvals: Watermark Level 1. WM74556.

Standard: AS/NZS 4441: Oriented PVC (PVC-O) pipe for pressure applications.

Certified to AS/NZS 4020: Suitable for contact with drinking water.

Rubber ring seal with navy blue identifying strip.

